

T2-C

Full Capacity Digital Tabletop Press



The first tabletop press designed with the full capacity of a larger press. Utilizing all the capabilities of the T2 Digital Press, the **T2-C** easily fits into any size print department, producing consistent, high-volumes at 24/7 production. Having the option to print pre-die cut blanks or print on continuous material, the **T2-C** is ideal for brand owners, print shops, and smaller label converters looking to add high-resolution color inkjet labels to their portfolio.

- High print speed up to 12 inches per second (60 ft per minute)
- Superior print resolution up to 1600 dpi
- Print width 2" to 8.8"
- First tabletop press to operate at high-volume capacity and precision of a digital press

Technical Specifications

Operation

Print Resolution	1600 x 800 dpi or 1600 x 1600 dpi
Print Speed	6 ips (152 mm/sec) or 12 ips (300 mm/sec)
Print Area	Width: 8.8" (223 mm) Length without stitching: 0.6" – 30" (15 mm – 762 mm) Length with stitching: Unlimited
Media Sensors	Optical tracking edge sensor, adjustable position. Black mark sensor, gap sensor and continuous
Connectivity	Ethernet 10/100/1000
Driver	Microsoft® Windows 10, 8, 7, Windows Server® 2012, 2008, 64/32-bit drivers
Software	TrojanControl Software, Microsoft Windows® 10, 8, 7; Windows Server® 2012, 2008, 64/32-bit Drivers
Slitting Station	(3) slitter blades included by default, up to (7) slitter blades may be installed and used Slitting not allowed for continuous material Cardboard cores with measuring (label width + edge trim) should be ordered.

Environment & Physical

Conditions for Operation	Between 59° F – 86° F (between 15° C – 30° C) at RH 22 to 80% (non-condensing)
Conditions for Storage	Between 41° F – 122° F (5° C – 50° C) at RH up to 85%, non-condensing at 149° F (65° C)
Power Requirements	100-240V AC – 50/60 Hz (360W, 2.5A power supply)
Aerosol Extraction System	Replaceable filters
Dimensions	With 2 Liter external ink tanks: 23.8" L x 22.8" W x 31.3" H (606 mm x 580 mm x 795 mm)
Touchscreen	Touchscreen Display
Weight	132.3 lbs. (60 kg) without supplies

Supplies

Ink Type	High Performance water-based dye ink Four 2-liter tanks CMYK
Label Width	1.9" – 9.8" (50 mm – 250 mm)
Length (Die-cut)	0.6" – 60" (15 mm – 1525 mm)
Thickness	4 pt/mil – 12 pt/mil
Roll Size	Core: 3" (76 mm) Max. OD: 11.8" (299.7 mm)
Types	Paper, Ink jet coated gloss paper, PE, PET, PP

Maintenance

Maintenance Cartridge	Maintenance tray with replaceable modules (wiper roller/print head cap)
Aerosol Extraction System	Replaceable filters

Warranty

One-Year Manufacturer's Parts & Labor Warranty (excludes wear parts and supplies)



Toll-free: 877-757-7978 | Tel: 401-828-4000 | trojanlabel@astronovainc.com | astronovaproductid.com