

QL-30  
QL-60



## One-Color Thermal Transfer Printers



Compact, monochrome high-speed thermal transfer printers that are designed with ease of use in mind. The **QL-30** at 300 dpi and the **QL-60** at 600 dpi are both high-quality printers that offer high print speeds of up to 11.8 inches per second. Perfect for barcode label printing, or for printing one-color labels that are exposed to extreme conditions for long periods. Both printers can be operated in stand-alone mode, in a PC application or a network.

These printers are an ideal solution for producing labels for hazardous substances, including barcoding, cardboard boxes, pallets, and more.

- High print speed up to 11.8 inches per second (55 ft per minute)
- Print resolution up to 300 or 600 dpi
- Print width 0.1" to 4.2"
- Mono-color, industrial application with immediate label output
- Compact design thermal transfer label printer

# Technical Specifications

## Operation:

<b>Ink Type:</b>	Thermal transfer
<b>Print Resolution:</b>	QL-30: 300 dpi QL-60: 600 dpi
<b>Print Speed:</b>	QL-30: 1 ips (20 mm/sec) 11.8 ips (300 mm/sec) QL-60: 1 ips (20 mm/sec) 5.9 ips (150 mm/sec)
<b>Print Area:</b>	Width: 0.2" (4 mm) – 4.2" (106 mm) Length: 0.1" (3 mm) – 78.7" (2000 mm)
<b>Media Sensors:</b>	Gap, Reflective, Continuous
<b>Connectivity:</b>	High-Speed USB 2.0; Gigabit Ethernet; RS-232 (1,200 - 230,400 baud) (2) USB host device on rear panel (for keyboard, scanner, USB memory, bluetooth adapter) (1) USB host device on operation panel (for USB memory or service key) 802.11b/g/n WLAN , Digital I/O with 8 in- and outputs
<b>Software:</b>	Microsoft® Windows 10, 8, 7; Windows Server® 2012, 2008, 64/32-bit Drivers, CQL Pro advanced label creation and print management software Nicelabel® Enterprise or Desktop Software (optional)

## Environmental & Physical:

<b>Printer Operating:</b>	32° F to 105° F (0° C to 40° C), 10% to 85% Relative Humidity (non-condensing)
<b>Power Requirements:</b>	100 - 240 VAC 50/60Hz, 1.5A/0.5A
<b>Dimensions:</b>	18.1" L x 9.9" W x 11.3" H (460 mm x 252 mm x 288 mm)
<b>Weight:</b>	22 lbs. (10 kg) without supplies
<b>Optional Accessories:</b>	Label Rewinder, Label Unwinder, Cutter, Cutter/Stacker, Present Sensor

## Supplies:

<b>Ribbon Supplies:</b>	Each roll 1,476 ft. long (450 m)
<b>Ink Type:</b>	Thermal transfer

## Labels and Tags:

<b>Width:</b>	0.2" (4 mm) – 4.3" (110 mm)
<b>Length:</b>	0.1" (3 mm) – 78.7" (2,000 mm)
<b>Thickness:</b>	2.3 – 28.7 mil (0.06 mm - 0.73 mm)
<b>Roll Size:</b>	8.1" OD (205 mm), 1.5" (38 mm) – 3.9" (100 mm) ID
<b>Types:</b>	Gloss Paper, Matte Paper and Synthetic pressure-sensitive; Paper Tag Stock

## Warranty:

One-Year Manufacturer's Parts & Labor Warranty on printer (excludes wear parts and supplies)



 **QuickLabel**® *The Labels You Want When You Need Them.*®

Toll-free: 877-757-7978 | Tel: 401-828-4000 | [info@quicklabel.com](mailto:info@quicklabel.com) | [www.quicklabel.com](http://www.quicklabel.com)